

## ALLEN HEX KEY SIZES

by Bob Vaughan

6/7/15 TPS

NOMINAL SIZE	NOMINAL FLATS	NOMINAL POINTS	MEASURED AT POINTS	TIGHT FIT	LOOSE FIT
				USE DRILL	

0.050	0.0500	0.0577	0.055	53	1/16
1/16	0.0625	0.0722	0.069	49	5/64
5/64	0.0781	0.0902	0.087	43	3/32
3/32	0.0938	0.1083	0.105	36	7/64
7/64	0.1094	0.1263	0.123	1/8	30
1/8	0.1250	0.1443	0.141	27	26
9/64	0.1406	0.1624	0.158	21	19
5/32	0.1562	0.1804	0.177	15	13
3/16	0.1875	0.2165	0.213	7/32	2
7/32	0.2188	0.2526	0.248	1/4	F
1/4	0.2500	0.2887	0.282	L	M
5/16	0.3125	0.3608	0.357	23/64	U
3/8	0.3750	0.4330	0.425	11 MM (7/16)	7/16
7/16	0.4125	0.4763	0.501	13 MM	33/64
1/2	0.5000	0.5774	0.575	37/64	19/32

1.5 MM	0.0591	0.0682	0.065	51	50
2.0 MM	0.0787	0.0909	0.087	43	42
2.5 MM	0.0984	0.1137	0.111	33	32
3 MM	0.1181	0.1364	0.132	29	28
4 MM	0.1575	0.1818	0.177	15	14
5 MM	0.1969	0.2273	0.223	1	4
6 MM	0.2362	0.2728	0.267	I	7 MM
8 MM	0.3150	0.3637			